

SPECIFICATIONS

| TYPE | | COOLING MODEL | | | | HEAT & COOL MODEL | | | | | |
|-----------------------|-------------------|-----------------|-----------|------------------|------------------|-------------------|---------------|----------------------|----------------------|-------------|------|
| INDOOR UNIT | | KF-65P/A1 | KF-75P/A1 | KF-100P/A1-34005 | KF-120P/A1-34005 | KFR-65P/A(d)1 | KFR-75P/A(d)1 | KFR-100P/A(d)1-34005 | KFR-120P/A(d)1-34005 | | |
| OUTDOOR UNIT | | KF-65W/A1 | KF-75W/A1 | KF-100W/A1-34005 | KF-120W/A1-34005 | KFR-65W/A(d)1 | KFR-75W/A(d)1 | KFR-100W/A(d)1-34005 | KFR-120W/A(d)1-34005 | | |
| COOLING CAPACITY | | W | 6500 | 7500 | 10000 | 12000 | 6600 | 7500 | 10000 | 12000 | |
| | | BTU/h | 22200 | 25600 | 36851 | 41000 | 22500 | 25600 | 34150 | 40980 | |
| HEATING CAPACITY | | W | - | - | - | - | 7000/9100 | 8000/10100 | 11000/14600 | 13000/16600 | |
| | | BTU/h | - | - | - | - | 23900/31050 | 27300/34500 | 37570/49870 | 44400/56700 | |
| CURRENT | COOLING | A | 12.2 | 13.8 | 6.7 | 8.2 | 11.7 | 14.0 | 7.2 | 8.4 | |
| | HEATING/HEATER | A | - | - | - | - | 10.4/20 | 12.9/22.5 | 6.7/12.2 | 8.5/14 | |
| POWER INPUT | COOLING | W | 2600 | 2750 | 3548 | 4548 | 2500 | 2800 | 3850 | 4910 | |
| | HEATING/HEATER | W | - | - | - | - | 2200/4300 | 2500/4600 | 3800/7400 | 4910/4900 | |
| POWER | | ~220~230V-50Hz | | 3N~400V-50Hz | | ~220~230V-50Hz | | 3N~400V-50Hz | | | |
| COMPRESSOR | | Hermitic-rotary | | Hermitic-scroll | | Hermitic-rotary | | Hermitic-scroll | | | |
| AIR FLOW VOLUME | m ³ /h | 1400 | | 2040 | | 1400 | | 2040 | | | |
| STATIC PRESSURE | | Pa | | 50 | | 50 | | 50 | | | |
| NOISE | INDOOR UNIT | dB(A) | | 43 | | 45 | | 43 | | 45 | |
| | OUTDOOR UNIT | dB(A) | | 59 | | 62 | | 59 | | 62 | |
| REFRIGERANT | | Kg | | R22 | | R22 | | R22 | | R22 | |
| | | Kg | | 1.85 | 2.25 | 3.4 | 3.6 | 2.1 | 2.5 | 3.5 | 3.8 |
| CONNECT PIPE DIAMETER | LARGE PIPE | inch | 5/8" | | 3/4" | | 5/8" | | 3/4" | | |
| | SMALL PIPE | inch | 3/8" | | 1/2" | | 3/8" | | 1/2" | | |
| INDOOR UNIT | WIDTH | | mm | | 1159 | | 1395 | | 1395 | | |
| | DEPTH | | mm | | 656 | | 656 | | 656 | | |
| | HEIGHT | | mm | | 260 | | 260 | | 260 | | |
| | WEIGHT | | Kg | | 37 | 49 | 37 | 49 | 37 | 49 | |
| | FLANGE | LENGTH | mm | | 918 | | 1155 | | 918 | | 1155 |
| WIDTH | | mm | | 207 | | 207 | | 207 | | 207 | |
| OUTDOOR UNIT | WIDTH | | mm | | 950 | | 950 | | 950 | | |
| | DEPTH | | mm | | 412 | | 412 | | 412 | | |
| | HEIGHT | | mm | | 700 | 840 | 1250 | 700 | 840 | 1250 | |
| | WEIGHT | | Kg | | 59 | 75 | 112 | 59 | 75 | 112 | |
| DRAIN HOSE DIAMETER | | mm | | 30 | | 30 | | 30 | | 30 | |
| DEHUMIDIFYING | | Kg/h | | 1.85 | 2.9 | 3.9 | 5.4 | 1.7 | 2.8 | 3.7 | 5 |

- The data listed above is subject to change without notice.
- Please refer to the nameplate for actual data.
- The air flow volume is measured at 0 external static pressure.